

Portable Baby Cam

Portable VS Series is an AV to TV converter with an integrated Wireless. It can transmit the Video and Audio Signal to the portable LCD Receiver. It is ideal for STB/DVD/VCD movie viewing, baby/patient monitoring.

VS-23/24 Series

Features:

- Wide-Band FM Modulation,4 Channel System.
- 1.7" TFT-LCD Screen.
- Portable Receiver Provides You More Flexibility.
- Camera :IR LEDs for night are selectable.
- Surveillance or Baby Monitoring.
- Operating Range: Up to 100m at Open Site.
- LED Indicates Battery Low Voltage.
- Ch1...Ch4 Scan in Auto Site.
- Apply Earphone via Earphone Socket.
- Adjustable Volume ,Brightness etc...
- With Alarm Function.



VS-25 Series

Features:

- 2.4GHz Wireless Surveillance System with PLL Circuit Design.
- Wide-Band FM Modulation.
- 4 Channel Selection to Avoid Interference.
- 6 IR LEDs Provide Bright View for Darkness.
- 1/3" color CMOS Image Sensor 64° Fixed Wide-Angle Lens.
- 380 TV Lines Clear Picture Display.
- 2.5" LCD Screen Display for Vivid and Bright Images.
- Channel Scan and Skip for Multi-Camera Usage.
- Remote Pan & Tilt Control Auto or Manually Pan: $\pm 90^\circ$;Tilt: $\pm 30^\circ$.
- Small Palm Size of Receiver for Mobile Usage.
- Operating Range: Up to 100m at Open Site.

Transmitter	VS-23T	VS-24T	VS-25T
Frequency Band	2.4~2.4835GHz		
RF Output Level(Max.)	0dBm / FCC, 10dBm / CE		
Modulation	FM (Audio / Video)		
Image Sensor	-	-	1/3" CMOS, PAL
Lens	-	-	F 1.8/f6.0mm 64° wide angle
Auto Iris	-	-	1/60~1/6,000sec
Picture Element	628(H)x582(V)		
Picture Resolution	380 TV Lines		
Min. Illuminations	1 lux		0.5 lux (LED on)
Microphone	Electrical Condenser		
CH/Low Voltage Indicate	LED(Red)		
Channel Select	Switch		
Power Supply	7.5VDC,500mA or 3AA battery	7.5VDC,500mA or 2AA battery	9VDC,600mA

Receiver	VS-23R	VS-24R	VS-25R
Sensitivity	-80dBm		
IR Extending Frequency	433.92MHz		
IR Receiving Range	More then 8m		
Output Port	3.5mm jack		
Earphone Output Port	3.5mm stereo jack		
Channel Operating Mode	-	-	Auto / Manual Scan
LCD Screen Size	1.7" TFT-LCD		2.5" TFT-LCD
Mode	Alarm / Normal		-
Alarm Sound Level	60dB@30cm transmitter		-
CH/Low Voltage Indicate	LED(Red)		
Channel Select	Button with LED indicated		
Power Supply	5VDC,1A or 3AA battery	5VDC,1A or 3AA battery	5VDC,1000mA